

Maintenance Instruction of Water Products

How to repair the damaged water products

A: Repair needle eyes

If your water products are damaged by needle or the similar small cone-shape products, it's very easy to repair.

1. Cover the inflating valve after deflating the products to reduce the recycle of the air inside of the products.
2. Take out the glue from the repair kits, drip glue to the needle eye.
3. If the needle eye is relatively large, put the toothpick dipped glue to the damaged needle eye, then smearing the needle eye with glue
4. Repaired, to inflate after 4 hours

B: To repair the cut or spoiled by high heating

1. Cover the inflating valve after deflating the products to reduce the recycle of the air inside of the products.
2. Take out the repair material to cut a suitable patch for the cut.
3. Smear the glue around damaged cut, put the patch on it, then smear the side by glue.
4. Press the patch to assure there is no rip on the patch, to flat the patch by smooth heavy things.
5. To inflate after 8 hours, then repaired is done.

C: Lint repair

If there is lint broken in the inner layers, please repair as follow process

1. Clear the damaged space by clean water, cut the thread ends.
2. Take out the patch to cover the damaged space, the patch can be a little bigger than the damaged.
3. Smear the glue on the damaged space and patch; paste the edge to assure the total paste.
4. Press the patched space to level by smooth heavy things.
5. To inflate the products after 24 hours pressing repaired.

Special instructions

Did water products are air leakage?

Any water products (including tire) will leak air naturally, which is normal. Generally to re-inflating every 5 or 7 days .